

CYNPOL LL6217

Linear Low Density Polyethylene Resin

Product Description

CYNPOL LL6217 is a Hexene linear low density polyethylene for film extrusion. This product is designed for excellent draw down and puncture strength. It is barefoot grades without additives.

Applications

Stretch-wrap and co-extrusions film, liners, heavy duty bags, trash bags, freezer film.

Requirement meets

CYNPOL LL6217 meets the requirements of the U.S. Food and Drug Administration as specified in 21 CFR 177.1520 which is covering safe use of polyolefin articles intended for food contact.

Physical Properties

Property ¹	Test Method	Unit	Typical Value	Reference
Melt Index	ASTM D-1238	g/10min	2.0	2.16kg at 190 °C
Density	ASTM D-792	g/cc	0.917	
Tensile Strength, Break	ASTM D-882	MPa	MD 48 TD 32	
Elongation	ASTM D-882	%	MD 430 TD 700	
Haze	ASTM D-1003	%	2.5%	
Elmendorf Tear	ASTM D-1922	g	MD 250 TD 550	
Dart Drop Impact Strength, F50	ASTM D-1709	g	80	

¹The technical information on film properties is based on blown film 20µm thickness and all data information herein refers to typical values. Since conditions of product use is outside our control, we make no warranties and assume no liability in connection with any use of this information.



For technical support & more information

16825 Northchase Drive, Suite 1400, Houston, Texas 77060 USA T +1.281.618.1300 F +1.281.618.1398 admin@vinmar.com www.vinmar.com

We make no other representation or warranties, express or implied, including, without limitation, warranties of merchantability and fitness for a particular purpose, and expressly disclaims all other representations and warranties and any and all other obligations or liabilities on the part of us. No person is authorized to give any other warranties or to assume any other liability on behalf of us unless made or assumed in writing by us.

Revised March 2018